

C2 The twinned pillars (4) for their part are welded to the floor frame (1) and the ceiling frame (6) with the help of junction gussets absorbing and transmitting the shearing force of the building. The number of twinned pillars required is determined by the statics.

On page 5, lines 25-28, please replace the paragraph to read as follows:

C3 Perpendicular to the longitudinal direction of the ceiling frame, several C 60 or C 80 transverse bearer (7) are welded inside the frame, the distance between them depending upon static requirements; they support the substructure of the suspended ceiling or the roof.

IN THE CLAIMS

Please cancel Claim 17 and replace Claims 2-14 and 16-20 to read as follows:

C3
C4 2. Prefabricated buildings or houses according to claim 20, wherein the floor frame comprises a standardized steel section C 160, St 37 or St 52 and at least one other possible section, wherein the section is beveled and welded.

3. Prefabricated buildings or houses according to claim 20, wherein the flanges are welded on the inside of the floor frame in a well-defined axial distance in order to fill an incurved part of the flange with concrete without reinforcing the latter.

E3
cont
4. Prefabricated buildings or houses made by a modular steel frame construction method, the prefabricated buildings or houses comprising:

- a) a ceiling frame,
- b) a floor frame;
- c) Z-shaped sections welded inside the floor frame; wherein the Z-shaped sections form flanges; and
- d) at least one pair pillar, wherein the pillar comprises a first section and a second section, wherein the first section is connected to the floor frame and the second section is connected to the ceiling frame; wherein the sections are interconnected by the use of a transverse bearer and pins

Cd
wherein the floor layer consists of concrete having a "d" of at least 100 mm, and undermost of an insulating layer of pressed rockwool or a similar insulation material having a "d" of at least 60 mm, wherein the floor layer is mounted between the flanges and the floor layer is covered, without being reinforced, with B 25 or a concrete of superior proficiency grade.

5. Prefabricated buildings or houses according to claim 20, wherein the sections of the pillar consists of MSH sections 60/60/5, St 37 or St 52 and at least one other conceivable sections and that they are interconnected by welded steel bridges 80/80/10 or other variants in dependence of the chosen section, and in an axial distance from each other conforming to the statics specifications.

6. Prefabricated buildings or houses according to claim 20, wherein the sections are connected to the floor frame and the ceiling frame through junction gussets in conformity with statics specifications.

7. Prefabricated buildings or houses according to claim 20, wherein the number of the pair of pillars is determined by statics requirements.

8. Prefabricated buildings or houses according to claim 20, wherein the pins consist of solid turned bars of St 37 or other conceivable materials, and that they are used for connecting vertically the sections of the pillars and to connect a first module and a second module placed one on top of another.

9. Prefabricated buildings or houses according to claim 20, wherein the combination of the sections of the pillars with the pins provides accurate vertical and horizontal structure of the building by means of a simple plug-in connection.

10. Prefabricated buildings or houses according to a modular steel frame construction method as claimed in claim 20, wherein the ceiling frame comprises an L-shaped sheet-steel section, St 37 or 52 or of other conceivable materials or sections.

11. Prefabricated buildings or houses according to a modular steel frame construction method as claimed in claim 20, wherein the ceiling frame consists of an edged or rolled L-section 250/75/5 or other conceivable sections.

12. Prefabricated buildings or houses according to claim 20, wherein the frames are beveled and welded at their angles or corners.

C3
cont
13. Prefabricated buildings or houses according to claim 20, further including C 60, C 80 or other sections welded into the ceiling frame perpendicular to a longitudinal direction of the ceiling frame and in an axial distance depending upon statics specifications.

C4
14. Prefabricated buildings or houses according to claim 20, wherein the combination of the ceiling frame with the floor frame generates a beam allowing a cantilever span of up to 14 m.

C3
cont
16. Prefabricated buildings or houses according to claim 20, further including at least a pair of beams interconnected either by screw-bolts or through welding, the method of interconnection depending upon a cantilever span.

C5
18. Prefabricated buildings or houses made by a modular steel frame construction method, the prefabricated buildings or houses comprising:

- a) a ceiling frame,
- b) a floor frame ;
- c) Z-shaped sections welded inside the floor frame; wherein the Z-shaped sections form flanges; and

63
C3
C4
C5
C6
C7
C8
C9
C10
C11
C12
C13
C14
C15
C16
C17
C18
C19
C20
C21
C22
C23
C24
C25
C26
C27
C28
C29
C30
C31
C32
C33
C34
C35
C36
C37
C38
C39
C40
C41
C42
C43
C44
C45
C46
C47
C48
C49
C50
C51
C52
C53
C54
C55
C56
C57
C58
C59
C60
C61
C62
C63
C64
C65
C66
C67
C68
C69
C70
C71
C72
C73
C74
C75
C76
C77
C78
C79
C80
C81
C82
C83
C84
C85
C86
C87
C88
C89
C90
C91
C92
C93
C94
C95
C96
C97
C98
C99
C100

d) at least one pair pillar, wherein the pillar comprises a first section and a second section, wherein the first section is connected to the floor frame and the second section is connected to the ceiling frame;
wherein the sections are interconnected by the use of a transverse bearer and pins
wherein the modules are connected, mounted and welded at the building site.

19. Prefabricated buildings or houses according to claim 20, wherein the buildings or houses include several stories.

20. Prefabricated buildings or houses made by a modular steel frame construction method, the prefabricated buildings or houses comprising:

- a) a ceiling frame,
- b) a floor frame ;
- c) Z-shaped sections welded inside the floor frame; wherein the Z-shaped sections form flanges; and
- d) at least one pair pillar, wherein the pillar comprises a first section and a second section, wherein the first section is connected to the floor frame and the second section is connected to the ceiling frame;
wherein the sections are interconnected by the use of a transverse bearer and pins; wherein the ceiling frame, the floor frame, and the at least one pair of pillar form a module; and